




Easy as 1, 2, 3



Step 1 - Turn the laminator control to your desired setting.



Step 2 - Feed the ProSEAL pouch through the laminator.



Step 3 - Your finished print in one easy step!

The ProSEAL[®] One Step Sign & Display System

The ProSEAL laminator's simple, one-step operation, smooth performance and minimal maintenance, makes it an ideal laminator for businesses looking to produce professional display graphics for the first time.

With its low start up cost, the ProSEAL Laminator takes up little space and requires no specialist skills to use and maintain, making mounting and laminating quick and easy. When used with the ProSEAL consumables range of Pouch Boards and Flexible Pouches, you'll be amazed at how easy it is to extend your presentation graphics capability and make the most of your prints.

One Great Solution...the Choice of Two Great Machines

To meet a variety of pouch, mounting board and image size requirements, the ProSEAL Laminator is offered in a choice of two models. The ProSEAL 25 is suitable for ProSEAL materials up to 25" (635mm wide) and ProSEAL 44 is suitable for ProSEAL materials up to 44" (1118mm wide). Both models offer the same great features and capabilities that make the ProSEAL Laminator the perfect mounting and laminating solution for businesses looking to extend their print finishing services or for in-house use.

For further information on ProSEAL consumables, please refer to the ProSEAL Mounting and Laminating Pouch Boards & Flexible Pouches leaflet.



FEATURES:

- Space-saving design for convenient fit on work-table
- Single control operation lets you select thickness settings of your ProSEAL materials
- Automatic pressure and temperature settings
- Reverse mode allows misfeeds to be cleared quickly and easily
- Silicone rollers and easy-clean features mean minimal maintenance
- 1-year warranty when used with ProSEAL consumables

Technical Specifications

	ProSEAL 25	ProSEAL 44
Part Number	60794	60853
Maximum Width	25" (635 mm)	44" (1118 mm)
Maximum Temperature	155 - 160° C (311 - 320° F)	155 - 160° C (311 - 320° F)
Maximum Speed	1.0 fpm (305 mm/min)	1.0 fpm (305 mm/min)
Maximum Pressure	1 N/mm	0.8 N/mm
Electrical	220/240VAC/50Hz 7A	220/240VAC/50Hz 9A
Thickness Settings	0 (rollers closed) 1.5 mm (1/16") 3 mm (1/8") 5 mm (3/16") 6 mm (1/4")	0 (rollers closed) 1.5 mm (1/16") 3 mm (1/8") 5 mm (3/16") 6 mm (1/4")
Dimensions (WxHxD)	40" x 12" x 15" (1016 x 305 x 380mm)	58" x 12" x 15" (1473 x 305 x 380 mm)
Net Weight	77 lb. (35 kg)	154 lb. (70 kg)
Shipping Weight	90 lb. (41 kg)	172 lb. (78 kg)
Safety Certifications	cETL, CE	cETL, CE

SEAL[®] Brands and ProSEAL[®] are registered trademarks of SEAL Graphics



SEAL Graphics Americas
7091 Troy Hill Drive
Elkridge
MD 21075
U.S.A
Tel: (410) 379 5400
Fax: (410) 379 8960

SEAL Graphics UK Ltd
1 Watkins Close,
Burnt Mills Industrial Estate
Basildon, Essex SS13 1BJ
United Kingdom
Tel: + 44 1268 530 331
Fax: + 44 1268 725 864

SEAL Graphics Europe BV
Kanaaldijk O.Z. 3
P.O. Box 29,
8100 AA Raalte
The Netherlands
Tel: + 31 572 345 500
Fax: + 31 572 345 501

SEAL Graphics Pacific Limited
Unit A, 13th Floor, Block 1
Leader Industrial Centre
Tsuen Wan,
New Territories,
Hong Kong
Tel: + 852 2407 3738

Contact your local distributor: