

Stoptlight backing films offer a range of unique light-blocking film solutions for finishing portable display systems. Available in different thicknesses and adhesive formulations, these backing films provide the ultimate finishing result for the Pop-Up and Roll-Up display market.

STOPLIGHT 115

This heat-activated film has been designed especially for the Roll-Up displays and Banner stands. It is specifically designed with an essential light-blocking core. When used in conjunction with Jet Guard Crystal Matte it provides the ultimate, high quality finishing solution.

PS STOPLIGHT 115

This pressure sensitive film has been designed especially for the Roll-Up displays and Banner stands. It allows users with cold lamination facilities to produce a profitable finishing solution in this display arena. Like all Stoptlight films it has an essential light blocking core. The water-based adhesive ensures a strong permanent bond to digital media and when used with Print Shield Deep Crystal, PS Stoptlight 115 has outstanding visual results.

STOPLIGHT 220

Ideal backing film for all Pop-Up Display systems, Stoptlight 220 is a high quality backing film providing a rigid, yet flexible opaque backing solution. Constructed with the SEAL patented aluminium core layer, it ensures no light can get through to distort the final image. The film has excellent lay flat memory and panels, once created, are easily rolled for storage. This heat-activated film is ideal for use on end and curved panels where flexibility is key and excellent results are achieved when used with Jet Guard Deep Crystal.

PS STOPLIGHT 220

This pressure sensitive film has been designed especially for users with cold lamination facilities to produce a profitable finishing solution in the Pop-Up Display arena. Like all Stoptlight films it contains an essential light-blocking core. The filmic release liner ensures a smooth high quality coating and minimises piping of liner. The water-based adhesive ensures a strong permanent bond to a range of digital media and is recommended with Print Shield Deep Crystal to achieve the best finishing results.



STOPLIGHT 320

This heat-activated rigid backing film is a key component for all Pop-Up Display systems. It provides the extra rigidity needed, making it the ideal solution for finishing the main front panels. Like Stoptlight 220, Stoptlight 320 is also constructed with the SEAL patented aluminium layer to ensure that no light can get through to distort the final image. The film has excellent lay flat memory and once panels are created they are easily rolled for storage. When used with Jet Guard Deep Crystal this film provides a high quality finish.

PS STOPLIGHT 320

This improved white pressure sensitive backing film is the latest addition to the SEAL Stoptlight range. It is ideal for use with a wide range of Pop-Up Display systems. PS Stoptlight 320 provides users, who prefer to work with pressure sensitive materials, the option to produce a profitable finishing solution. The white backing maintains white balance when using thin inkjet media. Like all other Stoptlight films it has the essential light-blocking core, which gives excellent lay flat results to reduce curl. The filmic release liner ensures a smooth high quality coating and minimises piping. The water-based adhesive ensures a strong permanent bond to a range of digital media and is ideal for use with Print Shield Deep Crystal.

Stoplight® Backing Films

Technical Specifications

	Stoplight 115	PS Stoplight 115	Stoplight 220	PS Stoplight 220	Stoplight 320	PS Stoplight 320
Adhesive Type	EVA	Water Based	EVA	Water Based	EVA	Water Based
Film Type	Metalised OPP	Metalised OPP	Polyester/ Aluminium	Polyester/ Aluminium	Polyester/ Aluminium	Polyester/ Aluminium
Total Film Construction	115 mic	107 mic	220 mic	180 mic	320 mic	305 mic
Bond	Permanent	Permanent	Permanent	Permanent	Permanent	Permanent
Recommended Speed	1 –1.5 mpm	1 –1.5 mpm	1 –1.5 mpm	1 –1.5 mpm	1 –1.5 mpm	1 –1.5 mpm
Recommended Temperature	95°C - 100°C 203°F - 212°F	Ambient 40°C / 104°F	95°C - 100°C 203°F - 212°F	Ambient 40°C / 104°F	95°C - 110°C 203°F - 230°F	Ambient 40°C / 104°F
Release Liner	N/a	Polyester	N/a	Polyester	N/a	Polyester
Winding	N/a	Liner in	N/a	Liner in	N/a	Liner in
Core Size	76mm (3")	76mm (3")	76mm (3")	76mm (3")	76mm (3")	76mm (3")

Order Codes & Roll Sizes

Order Codes			Roll Size			Order Codes			Roll Size		
Stoplight 115	61166	880mm x 50m	Stoplight 320	64100	880mm x 50m						
	61167	1040mm x 50m		64101	1040mm x 50m						
PS Stoplight 115	64143	880mm x 50m	PS Stoplight 320	64102	1295mm x 50m						
				64124	880mm x 50m						
Stoplight 220	13279	880mm x 50m	64125	1040mm x 50m							
	60086	1040mm x 50m									
	60760	1295mm x 50m									
PS Stoplight 220	60421	880mm x 50m									
	60416	1040mm x 50m									